

Energy saving rating

The values according to EN Norm 14501 indicate the added insulation and added heat reduction, on top of good quality double glazing with a U-value[#] of 1.2 W/m². K - when Duette[®] shades are used.

Product description

Transparent / Translucent		Heat reduction					Insulation					Sound absorption				
Cell width		≤ 5 %	> 5 %, ≤ 15 %	> 15 %, ≤ 25 %	> 25 %, ≤ 35 %	> 35 %	≤ 5 %	> 5 %, ≤ 15 %	> 15 %, ≤ 25 %	> 25 %, ≤ 35 %	> 35 %	> 0 %, ≤ 15 %	> 15 %, ≤ 30 %	> 30 %, ≤ 45 %	> 45 %, ≤ 60 %	> 60 %
		C	B	A	A+	A++	C	B	A	A+	A++	*	**	***	****	*****
Batiste	25 mm / 32 mm				✓				✓					✓		
Batiste	64 mm				✓				✓						✓	
Batiste Sheer	25 mm / 32 mm			✓				✓				✓				
Batiste Sheer	64 mm			✓				✓				✓				
Elan	25 mm / 32 mm				✓				✓					✓		
Elan	64 mm				✓				✓						✓	
Elan TOUR	25 mm / 32 mm				✓				✓					✓		
Eternity REX LIFE	25 mm / 32 mm				✓				✓					✓		
Mono	25 mm			✓					✓					✓		
Nordic REX LIFE	25 mm / 32 mm				✓				✓					✓		
Royale	25 mm / 32 mm				✓				✓					✓		
Stitch REX LIFE	25 mm / 32 mm				✓				✓					✓		
Unik REX LIFE	25 mm / 32 mm				✓				✓					✓		
Unik FR	25 mm				✓				✓					✓		

Room Darkening		Heat reduction					Insulation					Sound absorption				
Cell width		≤ 5 %	> 5 %, ≤ 15 %	> 15 %, ≤ 25 %	> 25 %, ≤ 35 %	> 35 %	≤ 5 %	> 5 %, ≤ 15 %	> 15 %, ≤ 25 %	> 25 %, ≤ 35 %	> 35 %	> 0 %, ≤ 15 %	> 15 %, ≤ 30 %	> 30 %, ≤ 45 %	> 45 %, ≤ 60 %	> 60 %
		C	B	A	A+	A++	C	B	A	A+	A++	*	**	***	****	*****
Batiste Architella [®] RD	32 mm					✓					✓			✓		
Batiste Architella [®] RD	64 mm				✓					✓					✓	
Elan Architella [®] RD	32 mm					✓					✓		✓			
Elan Architella [®] RD	64 mm				✓					✓					✓	
Elan RD	25 mm / 32 mm					✓				✓			✓			
Elan RD	64 mm					✓				✓			✓			
Mono RD	25 mm					✓				✓			✓			
Unik RD	25 mm / 32 mm					✓				✓			✓			
Unik RD FR	25 mm					✓				✓			✓			



Heat reduction class
A++, A+, A, B or C.
The higher the % the more heat reduction.



Insulation class
A++, A+, A, B or C.
The higher the % the more insulation from the cold.



Sound absorption class
★ ★ ★ ★ ★ ★ ★ ★ ★ ★
The higher the star rating, the more sound absorption.